

TRI-FORCE FR SCAFFOLD SHEETING



Introducing the Tri-Force FR Scaffold Sheeting from BLC Construction Supplies—a TS62 certified flame-retardant solution that combines cost-effectiveness with superior performance. Ideal for low-level applications with minimal risk of high winds and short-term projects, this high-quality polyethylene sheeting is versatile and weatherproof, suitable for both traditional and modular systems.

Our scaffold sheeting features a unique design with eyelet holes on a double-width reinforced band, ensuring durability and ease of installation. The eyelets remain sealed until used, effectively minimizing the impact of wind and rain. The Tri-Force FR Scaffold Sheeting is not only a practical choice but also offers a distinctive advertising opportunity for your company or brand.

Explore the possibilities of customization by opting for on-site bespoke graphic printing on these sheets and enhance the visual appeal of your construction site. Elevate your project with Tri-Force FR Scaffold Sheeting, the reliable and customizable solution for your scaffolding needs.



FEATURES

- Fire Retardant - Certificated TS62 Flame Standard
- Waterproof
- UV Resistant
- Reduces Noise Levels

TECHNICAL DATA

| PERFORMANCE DATA | |
|------------------|---------------------------|
| MATERIAL | CO-POLYMER LDPE |
| WEAVE | 10 X 10 MESH 670 dtex PET |
| TENSILE STRENGTH | 650/N50mm |
| EYELET STRENGTH | 750/N50mm |
| CONFORMS TO | BS7955-1999 |
| INSTALL TO | BS8410:2007 |
| INSTALL WITH | TOGGLE TIES |

| SPECIFICATIONS | | | |
|------------------|----------|-------------|----------|
| CODE | 300025 | 300064 | 300061 |
| ROLL SIZE | 2M X 45M | 2.25M X 40M | 3M X 45M |
| WEIGHT | 170gsm | 170gsm | 170gsm |
| GRADE | STD | STD | STD |
| REINFORCED BANDS | 3 | 3 | 4 |
| COVERAGE | 90M2 | 90M2 | 135M2 |

01179 828180 | OFFICE@BLCCS.CO.UK | WWW.BLCCS.CO.UK

UNIT F, MOTORWAY DIST CENTRE, AVONMOUTH WAY, AVONMOUTH, BRISTOL, BS11 9YT