BLC CONSTRUCTION SUPPLIES
PROVIDING THE COMPLETE SOLUTION

PRODUCT DATASHEET

PRODUCT TYPE: CUSTOM BRANDED
PRODUCT GROUP: SHEETING

TRIFORCE HD FR DIGIWRAP

DESCRIPTION

Tri-force FR Digiwrap 220gsm Scaffold sheeting is a Flame Retardant scaffold sheet that can be used on traditional or modular systems. This high quality polyethylene sheeting is versatile and weatherproof. Each sheet is designed with unique eyelet holes on a double width reinforced band. Meaning the eyelets remain sealed until used.

High quality bespoke graphics can be applied to the sheet to improve the look on site and offer a unique advertising potential for promoting your company or brand.

Install with the recommended White Bullet Toggle Ties

PERFORMANCE DATA

Material	220gsm Co-polymer LDPE
Weave	10x10mesh 1670 dtex
Tensile Strength	650/N50mm
Eyelet Strength	750/N50mm
Install to	BS8410:2007
Install with	Toggle Ties

SPECIFICATIONS

Code	Size	Weight	Grade	Bands	Coverage
300066	2m x 45m	250gsm	Super T	3	90m2
300067	2.25m x 40m	220gsm	Premium	3	90m2
300071	3m x 45m	220gsm	Premium	4	135m2

FEATURES

- Size: Available in 2m x 45m, 2.25m x 40m & 3m x 45m
- Weight: 20kgs, 30kgs per roll
- Full colour printing of logos & photos
- Finish: Double width high strength reinforced bands along the length of sheet

Bristol (Head Office): Unit F, Motorway Distribution Centre, Avonmouth Way, Avonmouth, Bristol, BS11 9YT
London: Unit 6, Watermill Business Centre, Edison Road,Enfield,London,EN3 7XF
01179 828180 | office@blccs.co.uk | www.blccs.co.uk
VAT No: GB916313345 | Registration No: 2677597